VYNCO

INDUSTRY RANGE

ANGLED PLUGS - ROUND

DATASHEET

	VIPA320	VIPA332	VIPA416	VIPA420	VIPA432	VIPA450	VIPA516	VIPA520	VIPA532	VIPA540	VIPA550
Number of Pins	3 Round	3 Round	4 Round	4 Round	4 Round	4 Round	5 Round	5 Round	5 Round	5 Round	5 Round
Rated Voltage (V)	250V	250V	500V	500V	500V	500V	500V	500V	500V	500V	500V
Rated Frequency (Hz)	50Hz										
Rated Current	20A	32A	16A	20A	32A	50A	16A	20A	32A	40A	50A
Operational Temperature	-20°C to +50°C										
Terminals	L, N, E		L1, L2, L3, Earth				L1, L2, L3, Neutral, Earth				
Terminal Screw Type	Slotted										
Max Cable Size	6mm²	16mm²	6mm²	6mm²	16mm²	16mm²	6mm²	6mm²	16mm²	16mm²	16mm²
Max Cable Overall Diameter	22mm	28mm	22mm		28mm		22mm		28mm		
Flexible Cable Option	3C - 6mm² HD	3C - 10mm² HD	4C - 6mm² HD		4C - 10mm² HD		5C - 6mm² HD		5C - 10mm² HD		
IP Rating	IP66										
Complies With	AS/NZS 3123										