



Lighting Experience

BAIDE METAL LAMPS (ZHONGSHAN) CO.,LTD.

Http:// www.gamailluminer.com

Tel: 86-760-28103889

Fax: 86-760-22823177

Page 1 of 3 Pages

Report No.: 165-W30

Test Time: 2018-1-23 10:23

Luminaire Property

Luminaire Manufacturer:

Luminaire Category: LED LIGHTING

Number of Lamps: 1

Current: 0.062 A

Power Factor: 0.963

Luminaire Description: 165-W30

Voltage: 220.2 V

Power: 13.20 W

Photometric Results

CIE Class: Direct

Measurement Flux: 1252.9 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H80.2

Vertical Diffuse Angle(50%): V80.4

Luminaire Efficacy Rating (LER): 95

Max. Intensity: 678.22 cd

Total Rated Lamp Lumens: 1252.9 lm


Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 677.63 cd

Pos of Max. Intensity: H270 V1

Picture Of Luminaire



Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 80.3° Unit: cd

— C0-C180 — C90-C270

C Plane (°): 0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°): 0.0-180.0: 1.0

Test Device: GPM-2000

Distance: 6.000 m

Humidity:

Inspector:



Lighting Experience

BAIDE METAL LAMPS (ZHONGSHAN) CO.,LTD.


Http:// www.gamailluminer.com

Tel: 86-760-28103889

Fax: 86-760-22823177

Page 2 of 3 Pages

Illuminance at a Distance



C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-2000

Distance: 6.000 m

Humidity:

Inspector:



Lighting Experience

BAIDE METAL LAMPS (ZHONGSHAN) CO.,LTD.

Http:// www.gamailluminer.com

Tel: 86-760-28103889

Fax: 86-760-22823177

Page 3 of 3 Pages

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
3H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
4H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
6H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
8H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
12H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
X=4H Y=2H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
3H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
4H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
6H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
8H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
12H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
X=8H Y=4H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
6H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
8H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
12H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
X=12H Y=4H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
6H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$
8H	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$	1.\$

Calculate in accordance with CIE 190:2010

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-2000

Distance: 6.000 m

Humidity:

Inspector: