



---

# CONNERY

---

WEATHERPROOF LED UNDER VERANDA



# CONNERY

- Operating Temperature -20°C to +35°C
- ABS Body and Polycarbonate Diffuser – 105mm H x 158mm W
- Emergency and Sensing options available
- Sensor unit spec: 360° detection angle, 1-8m Detection range, Time setting range: 10 sec – 10 min, Light control: 10-2000 Lux
- Emergency unit spec: 3 Hour Emergency Operation, Recharge time: 20 Hours, Intelligent automatic recharge function, Test switch with self-test function
- 50,000 Lifetime hours under normal conditions



Code	Power (W)	Lumens Output	Colour Temp (k)	Dimensions (mm)
<b>VU2</b>	24	2050	4000	658 x 158
<b>VU4</b>	45	3850	4000	1268 x 158
<b>VU5</b>	64	5450	4000	1568 x 158
<b>VU56</b>	64	5450	6500	1568 x 158

Code	Type	Power (W)	Lumens Output	Colour Temp (k)	Dimensions (mm)
<b>VU4E</b>	Emergency	45	3850* / 1155**	4000	1268 x 158
<b>VU4S</b>	Sensing	45	3850	4000	1268 x 158
<b>VU4ES</b>	Emergency & Sensing	45	3850* / 1155**	4000	1268 x 158
<b>VU5E</b>	Emergency	64	5450* / 1635**	4000	1568 x 158
<b>VU5S</b>	Sensing	64	5450	4000	1568 x 158
<b>VU5ES</b>	Emergency & Sensing	64	5450* / 1635**	4000	1568 x 158
<b>VU56E</b>	Emergency	64	5450* / 1635**	6500	1568 x 158
<b>VU56S</b>	Sensing	64	5450	6500	1568 x 158
<b>VU56ES</b>	Emergency & Sensing	64	5450* / 1635**	6500	1568 x 158

Made to order locally, short delays may occur. \* Standard Lumen Output \*\* When running on Emergency backup Lumen Output is 30% of standard Lumen Output