



DIGITAL INDICATORS IP65

MODEL	VOLTAGE	TEMP RANGE	INPUT TYPES	OUTPUTS
EI141-230	230V AC	-1999° to 4000° C	Analogue (V) or (mA)	Display only
EI141-SM	9-30VDC	-1999° to 4000° C	Analogue (V) or (mA)	Display only

TIMERS IP65

MODEL	VOLTAGE	INPUT MODES	OUTPUT MODES	OUTPUTS
ETM1411-230	230V AC	Start / Stop Extremal	Delay & Pulse	Relay (8A)

THERMISTERS

MODEL	SENSOR TYPE	CASING	CABLE TYPE	ENVIRONMENT
E-NTC-APS-1.5S	NTC	Stainless shell	Silicon	AIR
E-NTC-LPS-1.5S	NTC	Stainless shell	Silicon	LIQUID
E-NTCH-APS-1.5S	NTCH	Stainless shell	Silicon	AIR
E-NTCH-LPS-1.5S	NTCH	Stainless shell	Silicon	LIQUID

OPTIONAL ACCESSORIES

MODEL	ACCESSORY	COMPATIBLE	TYPE
3C0.000.200	Plug in communications board	All PID controllers	RS232
3C0.000.400	Plug in communications board	All PID controllers	RS485
100.3GB.000	CALgrafix process monitoring & setup software		
E-TRANSFORMER-12	230V to 12V Stepdown transformer	ET1312 / EDT1323	