



DESIGNED TO FIT INTO TIGHT ROOF SPACES.

We've taken our popular Jolie downlight and made it slimmer to fit in those tight roof spaces.

With a depth of just 47mm, the new Lopez fits perfectly under a ceiling truss.

Easy to install with quick connect terminals, or flex & plug (LOPEZF), the range has 3 colour settings, is dimmable and a 100° beam angle.

The Lopez downlights are safe to use around insulation with IP54, IC-F and IC-4 ratings, and is perfect for a wide range of applications.





LOPEZ SPECIFICATIONS

VOLTAGE: 200-240V AC

WATTAGE: 8W

LUMEN OUTPUT: 860-920lm

CRI: 80+

BEAM ANGLE: 100°

INGRESS RATING: IP54 (FRONT ONLY)

DIMMABLE: YES

DEPTH: 47mm

FASCIA SIZE: Ø 110mm

CUT-OUT SIZE: Ø 90mm

COLOUR TEMP: 3000K/4000K/5700K

LED LIFETIME: >40,000hrs

FEATURES: IC-F & IC-4 RATED

INTEGRATED DRIVER FLEX & PLUG (LOPEZF)







VYNCO

VYNCO.CO.NZ

Christchurch Office

388-396 Tuam Street Phillipstown, Christchurch 8011

PO Box 9022 Tower Junction, Christchurch 8149 P (+64) 3 379 9283 E sales@vynco.co.nz

Auckland Office

9 Levene Place Mt Wellington, Auckland 1061

PO Box 12 249 Penrose, Auckland 1642 P (+64) 9 525 6051 E sales@vynco.co.nz