
VYNCO



## M3G / M3GB - MCQUEEN DOWNLIGHT





SPECIFICATIONS	
Input Voltage	200 - 240V AC
Lumen Output	700 - 800lm
Efficacy	80lm/W
Colour Temperature	3000 / 4000 / 5700K
LED Lifetime Hours	40,000
IP Rating	IP20
IK Rating	IK06
Material	Aluminium + PC Diffuser

#### WARRANTY

This product is covered by the standard 3 Year Vynco Warranty - proof of purchase is required. Please contact Vynco for details of returns procedure.

**NOTE:** This product contains NO user serviceable parts.

#### WIRING

- A = Phase
- N = Neutral

# VYNCO INDUSTRIES (NZ) LIMITED

#### CHRISTCHURCH

388 Tuam Street, Phillipstown, Christchurch, 8011 PO Box 9022, Tower Junction, Christchurch 8149 New Zealand P +64 3 379 9283 F +64 3 379 6838 E sales@vynco.co.nz

## SAFETY

This product complies in full with AS/NZS 60598.2.2:2016.

This product should be installed by a suitably qualified person in accordance with Australian and New Zealand wiring rules.

This luminaire has been independently tested and is rated for IC-4 and IC-F installation.

### INSTALLATION PROCEDURE

Prior to installation, ensure desired location is suitable and clear of all obstructions.

#### STEP 1

Cut hole with suitable tool - check hole size before cutting. Check hole size before cutting - 90 to 95mm.

#### STEP 2

After ensuring circuit is isolated, terminate wiring in an approved manner.

#### STEP 3

Hold back the spring clips to insert in cut-out, then release the clips and centre the fixture.

#### STEP 4

Position the light to the desired angle.

#### STEP 5

Energise and test. Then select colour range using switch.

CW: 5700k NW: 4000k WW: 3000k

#### AUCKLAND

9 Levene Place, Mount Wellington PO Box 12 249, Penrose, Auckland 1061 New Zealand P +64 9 525 6051 F +64 9 525 5799

VYNCO.CO.NZ