




WPS1 / 1 POLE ISOLATOR

FEATURES

- Isolator switch 
- Padlockable
- IP66

WPS1


Switch Type	Lever Switch
Material	Polycarbonate
Colour	Grey
Box Size (L x W x D)	85 x 85 x 83mm
Padlockable	Yes / Off
IP Rating	IP66
Rated Voltage	250V AC
Rated Frequency	50Hz
Rated Current (Resistive)	20A
Switch Arrangement	Single Pole / 2 Way
Supplied With	Box fixing screw caps Lid fixing screw caps



WPS SERIES ISOLATORS

WPS120C / 2 POLE ISOLATOR

FEATURES

- Isolator switch 
- Padlockable
- IP66

WPS120C


Switch Type	Lever / Isolator
Material	Polycarbonate
Colour	Grey
Box Size (L x W x D)	85 x 85 x 83mm
Padlockable	Yes / Off
IP Rating	IP66
Rated Voltage	250V AC
Rated Frequency	50Hz
Rated Current (Resistive)	20A
Switch Arrangement	Double Pole / 1 Way
Supplied With	Box fixing screw caps Lid fixing screw caps



WPS SERIES ISOLATORS

WPS120 / 1 POLE ISOLATOR

FEATURES

- Isolator switch 
- Padlockable
- 2x captive polycarbonate screws
- IP66


WPS120

Switch Type	Lever / Isolator
Material	Polycarbonate
Colour	Grey
Box Size (L x W x D)	170 x 85 x 90mm
Padlockable	Yes / Off
IP Rating	IP66
Rated Voltage	250V AC
Rated Frequency	50Hz
Rated Current (Resistive)	20A
Switch Arrangement	Single Pole / 1 Way
Supplied With	2 x 25mm to 20mm Screw Reducer



WPS135 / 1 POLE ISOLATOR

FEATURES

- Isolator switch 
- Padlockable
- 2x captive polycarbonate screws
- IP66


WPS135

Switch Type	Lever / Isolator
Material	Polycarbonate
Colour	Grey
Box Size (L x W x D)	170 x 85 x 90mm
Padlockable	Yes / Off
IP Rating	IP66
Rated Voltage	250V AC
Rated Frequency	50Hz
Rated Current (Resistive)	35A
Switch Arrangement	Single Pole / 1 Way
Supplied With	2 x 25mm to 20mm Screw Reducer



WPS320 / 3 POLE ISOLATOR

FEATURES

- Isolator switch 
- Padlockable
- 2x captive polycarbonate screws
- IP66

WPS320


Switch Type	Lever / Isolator
Material	Polycarbonate
Colour	Grey
Box Size (L x W x D)	170 x 85 x 90mm
Padlockable	Yes / Off
IP Rating	IP66
Rated Voltage	415V AC
Rated Frequency	50Hz
Rated Current (Resistive)	20A
Switch Arrangement	Three Pole / 1 Way
Supplied With	2 x 25mm to 20mm Screw Reducer



WPS SERIES ISOLATORS

WPS335 / 3 POLE ISOLATOR

FEATURES

- Isolator switch 
- Padlockable
- 2x captive polycarbonate screws
- IP66

WPS335

Switch Type	Lever / Isolator
Material	Polycarbonate
Colour	Grey
Box Size (L x W x D)	170 x 85 x 90mm
Padlockable	Yes / Off
IP Rating	IP66
Rated Voltage	415V AC
Rated Frequency	50Hz
Rated Current (Resistive)	35A
Switch Arrangement	Three Pole / 1 Way
Supplied With	2 x 25mm to 20mm Screw Reducer