


### VGL150RW - REACHER GRILLE WITH LIGHT



IP20



#### SPECIFICATIONS

Input Voltage	200 - 240V AC
Duct Size	150mm
Typical Power	8W
IP Rating	IP24 (Light); IP20 (Driver)
Spigot Cutout	159mm

#### SAFETY

This product complies in full with AS/NZS 60695.11.5.

This product should be installed by a suitably qualified person in accordance with Australian and New Zealand wiring rules.

#### WARRANTY

This product is covered by the standard 3 Year Vynco Warranty - proof of purchase is required. Please contact Vynco for details of returns procedure.

**NOTE:** This product contains NO user serviceable parts.

#### WIRING

L = Phase (Red)

N = Neutral (Black)

#### INSTALLATION PROCEDURE

##### STEP 1

Separate the light grille from the base.

##### STEP 2

Select the desired colour temperature on CCT switch before installation.


CW = 5700K; NW = 4000K; WW = 3000K

##### STEP 3


Ensure desired location is suitable and clear of all obstructions. Cut a 159mm hole in the ceiling with a suitable tool.

##### STEP 4


After ensuring circuit is isolated, pull mains wiring down through 160mm hole.




STEP 1



STEP 2



STEP 3



STEP 4

#### VYNCO INDUSTRIES (NZ) LIMITED

##### CHRISTCHURCH

388 Tuam Street, Phillipstown, Christchurch, 8011  
PO Box 9022, Tower Junction, Christchurch 8149  
New Zealand

P +64 3 379 9283 F +64 3 379 6838

E sales@vynco.co.nz


**VYNCO.CO.NZ**

##### AUCKLAND


9 Levene Place, Mount Wellington  
PO Box 12 249, Penrose, Auckland 1061  
New Zealand

P +64 9 525 6051 F +64 9 525 5799

### VGL150RW - REACHER GRILLE WITH LIGHT



**STEP 5**



**STEP 6**


#### INSTALLATION PROCEDURE CONTINUED

##### STEP 5


Use a flat head screwdriver to remove the driver terminal cover, feed the main AC wire L.N. into the screw terminals respectively, then click cover back on.

##### STEP 6

Place driver and CCT switch in the ceiling space.



**STEP 7**



**STEP 8**

##### STEP 7


Pull the ducting down through the 160mm hole and tape the ducting onto the spigot with duct tape.

##### STEP 8


Push the ducting and spigot through the hole and fix in place with countersunk screws.

##### STEP 9

Connect the plug and socket, ensuring the cap is screwed tight. (Grille omitted from diagram for clarity).



**STEP 9**



**STEP 10**

##### STEP 10

Push the grille on the mounted spigot and twist clockwise until clips are tightly securing the grille in place.