

VMC ONE COMBINED METER BOARD

FEATURES

- Raised meter window
- Max meter depth of 115mm
- Box ahead available
- Top or bottom meter mounting



CODE	VMC117	VMC134	VMC151
DIN Capacity (Ways)	17 Ways	34 Ways	51 Ways
No. & Size of DIN Rail Rows	1 x Rows of 17	2 x Rows of 17	3 x Rows of 17
Earth Bar	1 x 12 Ways	1 x 30 Ways	1 x 40 Ways
Neutral Bar	1 x 8 Ways	1 x 14 Ways	1 x 22 Ways
RCD Neutral Bar	3 x 3 Ways	5 x 3 Ways	8 x 3 Ways
Base Box Dimensions (HxWxD)	445 x 355 x 109mm	754 x 355 x 109mm	754 x 355 x 109mm
Door & Surround Dimensions (HxWxD)	477 x 402 x 35mm	800 x 402 x 35mm	800 x 402 x 35mm
Overall Assembled Dimensions (HxWxD)	477 x 402 x 130mm	800 x 402 x 130mm	800 x 402 x 130mm
Total Internal Meter Mounting Space (HxWxD)	275 x 320x 124mm	275 x 320x 124mm	275 x 320x 124mm
Maximum Meter Depth	115mm	115mm	115mm
Operational Voltage	415V AC	415V AC	415V AC
Frequency (Hz)	50Hz	50Hz	50Hz
Max Current Rating (Amps)	100A	100A	100A
Short Circuit Withstand (kA)	10kA	10kA	10kA
Meter / Gear Tray Space (HxWxD)	275 x 320 x 115mm	275 x 320 x 115mm	275 x 320 x 115mm
Mounting	Flush/Surface		
Surface Mount Kit	VM34SK	VMCC	VMCC
Insulation Voltage (V)	1000V		
Base Box Material	Pre-galvanised Steel		
Door & Surround Material	Powdercoated Steel / PC		
IP Rating	IP40		
Designed to be Compliant to	AS/NZS 61439.3		
Colour	White		

VMC ONE COMBINED METER BOARD

FEATURES

- Raised meter window
- Max meter depth of 115mm
- Box ahead available
- Top or bottom meter mounting



CODE	VMC117BK	VMC134BK	VMC151BK
DIN Capacity (Ways)	17 Ways	34 Ways	51 Ways
No. & Size of DIN Rail Rows	1 x Rows of 17	2 x Rows of 17	3 x Rows of 17
Earth Bar	1 x 12 Ways	1 x 30 Ways	1 x 40 Ways
Neutral Bar	1 x 8 Ways	1 x 14 Ways	1 x 22 Ways
RCD Neutral Bar	3 x 3 Ways	5 x 3 Ways	8 x 3 Ways
Base Box Dimensions (HxWxD)	445 x 355 x 109mm	754 x 355 x 109mm	754 x 355 x 109mm
Door & Surround Dimensions (HxWxD)	477 x 402 x 35mm	800 x 402 x 35mm	800 x 402 x 35mm
Overall Assembled Dimensions (HxWxD)	477 x 402 x 130mm	800 x 402 x 130mm	800 x 402 x 130mm
Total Internal Meter Mounting Space (HxWxD)	275 x 320x 124mm	275 x 320x 124mm	275 x 320x 124mm
Maximum Meter Depth	115mm	115mm	115mm
Operational Voltage	415V AC	415V AC	415V AC
Frequency (Hz)	50Hz	50Hz	50Hz
Max Current Rating (Amps)	100A	100A	100A
Short Circuit Withstand (kA)	10kA	10kA	10kA
Meter / Gear Tray Space (HxWxD)	275 x 320 x 115mm	275 x 320 x 115mm	275 x 320 x 115mm
Mounting	Flush/Surface		
Surface Mount Kit	VM34SK	VMCC	VMCC
Insulation Voltage (V)	1000V		
Base Box Material	Pre-galvanised Steel		
Door & Surround Material	Powdercoated Steel / PC		
IP Rating	IP40		
Designed to be Compliant to	AS/NZS 61439.3		
Colour	Black		